




SECURE FIT



COMFORTABLE
STRETCH



CUT RESISTANCE

CUT E SLEEVES

FEATURES

- High stretch nylon material with 4-way stretch points to fit users' arms.
- Tapered design, wider on the bicep and tight on the wrist, to fit the natural arm form.
- Elastic band with non-slip dots on the bicep and stretch wrist cuff to keep the sleeves in place and prevent them from sagging.
- Breathable and lightweight material provides good dexterity and all-day comfort.
- Elastic thumb loop avoids pressure points when using gloves.
- Sun UV rays protection with UPF 50+ according to BS EN 13758-1:2002 +A1:2006 for the covered part of the arms.
- European Certified for cut protection: EN ISO 21420, EN388:2016 (3X42E), UKCA.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):

CUT LEVEL E (RED)

COLOR OF THE GLOVE:

GREY

MATERIAL:

HPPE, POLYESTER, GLASS FIBER, STEEL FIBER, SPANDEX, ELASTIC YARN

GAUGE:

13

SIZE RANGE:

CUT C SLEEVES - AVAILABLE IN SIZES 40CM AND 45CM

UNIT GUIDE

| DESCRIPTION | PACK QUANTITY | ARTICLE NUMBER |
|----------------------|---------------|----------------|
| CUT E SLEEVES - 40CM | 1 | 4932479936 |
| CUT E SLEEVES - 45CM | 1 | 4932479937 |



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



CUT E SLEEVES

CARE INSTRUCTIONS

- WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS
- NO CHEMICAL CLEANING
- DO NOT IRON
- DO NOT BLEACH
- NO TUMBLER

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer
Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



18 GAUGE



CUT RESISTANCE



SMARTSWIPE™



HI-DEX CUT B GLOVES

FEATURES

- 18 gauge material for extra dexterity and total mobility for precise task.
- Lightweight and thin gloves with polyurethane dipped palm.
- Excellent breathability and all-day comfort.
- Nitrile reinforcement between thumb and index finger for more durability.
- SMARTSWIPE™ fingertips - allows the use of touch screen devices without removing gloves.
- 5 times washable allowing extended lifetime, cost and waste reduction.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (3242B), UKCA, EAC, Ukraine.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):

CUT LEVEL <ATTRIB A="2684" L="10" O="555327"

COLOR OF THE GLOVE:

RED

MATERIAL:

HPPE, POLYESTER, NYLON, GLASS FIBER, SPANDEX.

COATING: POLYURETHANE (PU). REINFORCEMENT:

NITRILE

GAUGE:

18

SIZE RANGE:

HI-DEX CUT B GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

| SIZE | ARTICLE NUMBER | NO. OF PAIRS | ARTICLE NUMBER | NO. OF PAIRS |
|----------|----------------|--------------|----------------|--------------|
| 7 / S | 4932480491 | 1 | 4932480506 | 12 |
| 8 / M | 4932480492 | 1 | 4932480507 | 12 |
| 9 / L | 4932480493 | 1 | 4932480508 | 12 |
| 10 / XL | 4932480494 | 1 | 4932480509 | 12 |
| 11 / XXL | 4932480495 | 1 | 4932480510 | 12 |



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



HI-DEX CUT B GLOVES

CARE INSTRUCTIONS

- WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS
- NO CHEMICAL CLEANING
- DO NOT IRON
- DO NOT BLEACH
- NO TUMBLER

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer
Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



18 GAUGE



CUT RESISTANCE



SMARTSWIPE™



HI-DEX CUT C GLOVES

FEATURES

- 18 gauge material for extra dexterity and total mobility for precise task.
- Lightweight and thin gloves with polyurethane dipped palm.
- Excellent breathability and all-day comfort.
- Nitrile reinforcement between thumb and index finger for more durability.
- SMARTSWIPE™ fingertips - allows the use of touch screen devices without removing gloves.
- 5 times washable allowing extended lifetime, cost and waste reduction.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (3342C), UKCA, EAC, Ukraine.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):

CUT LEVEL <ATTRIB A="2684" L="10" O="555328"

COLOR OF THE GLOVE:

RED

MATERIAL:

RUBY, POLYESTER, NYLON, GLASS FIBER, SPANDEX.

COATING: POLYURETHANE (PU). REINFORCEMENT:

NITRILE

GAUGE:

18

SIZE RANGE:

HI-DEX CUT C GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

| SIZE | ARTICLE NUMBER | NO. OF PAIRS | ARTICLE NUMBER | NO. OF PAIRS |
|----------|----------------|--------------|----------------|--------------|
| 7 / S | 4932480496 | 1 | 4932480511 | 12 |
| 8 / M | 4932480497 | 1 | 4932480512 | 12 |
| 9 / L | 4932480498 | 1 | 4932480513 | 12 |
| 10 / XL | 4932480499 | 1 | 4932480514 | 12 |
| 11 / XXL | 4932480500 | 1 | 4932480515 | 12 |



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



HI-DEX CUT C GLOVES

CARE INSTRUCTIONS

- WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS
- NO CHEMICAL CLEANING
- DO NOT IRON
- DO NOT BLEACH
- NO TUMBLER

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer
Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



18 GAUGE



CUT RESISTANCE



SMARTWIPE™



HI-DEX CUT D GLOVES

FEATURES

- 18 gauge material for extra dexterity and total mobility for precise task.
- Lightweight and thin gloves with polyurethane dipped palm.
- Excellent breathability and all-day comfort.
- Nitrile reinforcement between thumb and index finger for more durability.
- SMARTWIPE™ fingertips - allows the use of touch screen devices without removing gloves.
- 5 times washable allowing extended lifetime, cost and waste reduction.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (3X42D), UKCA, EAC, Ukraine.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):

CUT LEVEL <ATTRIB A="2684" L="10" O="555329"

COLOR OF THE GLOVE:

RED

MATERIAL:

NYLON, HPPE, TUNGSTEN, SPANDEX. COATING: POLYURETHANE (PU). REINFORCEMENT: NITRILE

GAUGE:

18

SIZE RANGE:

HI-DEX CUT D GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

| SIZE | ARTICLE NUMBER | NO. OF PAIRS | ARTICLE NUMBER | NO. OF PAIRS |
|----------|----------------|--------------|----------------|--------------|
| 7 / S | 4932480501 | 1 | 4932480516 | 12 |
| 8 / M | 4932480502 | 1 | 4932480517 | 12 |
| 9 / L | 4932480503 | 1 | 4932480518 | 12 |
| 10 / XL | 4932480504 | 1 | 4932480519 | 12 |
| 11 / XXL | 4932480505 | 1 | 4932480520 | 12 |



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



HI-DEX CUT D GLOVES

CARE INSTRUCTIONS

- WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS
- NO CHEMICAL CLEANING
- DO NOT IRON
- DO NOT BLEACH
- NO TUMBLER

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



Disclaimer
Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeeeetool.eu



CUT RESISTANCE



WINTER



DEXTERITY



WINTER CUT B GLOVES

FEATURES

- Winter insulation and dual acrylic liner will keep the hand warm while working in cold conditions.
- Good grip performance in wet conditions due to the latex palm dipping and breathable back of hand.
- 15 Gauge in the outer liner and 10 gauge in the inner liner, allowing good dexterity.
- European Certified for cut and cold resistance protection: EN ISO 21420, EN388:2016 (2242B), EN511 (X1X), UKCA, EAC, Ukraine.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):

CUT LEVEL <ATTRIB A="2684" L="10" O="689133"

COLOR OF THE GLOVE:

RED

MATERIAL:

OUTER LINER: HPPE, GLASS FIBER, NYLON ELASTIC FIBER. INNER LINER: ACRYLIC TERRY. COATING: LATEX

GAUGE:

15,10

SIZE RANGE:

WINTER CUT B GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

| SIZE | ARTICLE NUMBER | PACK QUANTITY | ARTICLE NUMBER | PACK QUANTITY |
|----------|----------------|---------------|----------------|---------------|
| 7 / S | 4932480601 | 1 | 4932480606 | 12 |
| 8 / M | 4932480602 | 1 | 4932480607 | 12 |
| 9 / L | 4932480603 | 1 | 4932480608 | 12 |
| 10 / XL | 4932480604 | 1 | 4932480609 | 12 |
| 11 / XXL | 4932480605 | 1 | 4932480610 | 12 |



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



WINTER CUT B GLOVES

CARE INSTRUCTIONS



DO NOT IRON



NO CHEMICAL CLEANING



NO TUMBLER



DO NOT BLEACH



NO WASHING

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



CUT RESISTANCE



WINTER



DURABILITY



WINTER CUT D GLOVES

FEATURES

- Winter insulation and dual acrylic liner will keep the hand warm while working in cold conditions.
- Improved water permeability in wet environments due to a ¾ double latex dipping on palm and fingers.
- 15 Gauge in the outer liner and 10 gauge in the inner liner, allowing good dexterity.
- European Certified for cut and cold resistance protection: EN ISO 21420, EN388:2016 (3X43D), EN511 (X1X), UKCA, EAC, Ukraine.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):

CUT LEVEL <ATTRIB A="2684" L="10" O="689134"

COLOR OF THE GLOVE:

RED

MATERIAL:

OUTER LINER: HPPE, GLASS FIBER, STEEL WIRE, ELASTIC FIBER. INNER LINER: ACRYLIC TERRY. COATING: LATEX

GAUGE:

15,10

SIZE RANGE:

WINTER CUT D GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

| SIZE | ARTICLE NUMBER | PACK QUANTITY | ARTICLE NUMBER | PACK QUANTITY |
|----------|----------------|---------------|----------------|---------------|
| 7 / S | 4932480611 | 1 | 4932480616 | 12 |
| 8 / M | 4932480612 | 1 | 4932480617 | 12 |
| 9 / L | 4932480613 | 1 | 4932480618 | 12 |
| 10 / XL | 4932480614 | 1 | 4932480619 | 12 |
| 11 / XXL | 4932480615 | 1 | 4932480620 | 12 |



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeeool.eu



WINTER CUT D GLOVES

CARE INSTRUCTIONS



DO NOT IRON



NO CHEMICAL CLEANING



NO TUMBLER



DO NOT BLEACH



NO WASHING

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.


Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



CUT RESISTANCE



SMARTWIPE™



18 GAUGE



REINFORCEMENT



HIGH CUT F GLOVES

FEATURES

- Highest European cut level protection.
- 18 gauge material for extra dexterity.
- Excellent grip performance with nitrile dipped palm, material performs better than other materials in wide range of temperatures and oily surfaces.
- Excellent breathability and all day comfort.
- Nitrile reinforcement between thumb and index finger for more durability.
- SMARTWIPE™ palm and fingertips - allows the use of touch screen devices without removing gloves.
- DMF free and REACH compliance.
- 3 times machine washable.
- European Certified for cut protection: EN ISO 21420 and EN388:2016 (4X43F).

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):
CUT LEVEL F (PURPLE)

COLOR OF THE GLOVE:
PURPLE

MATERIAL:
HPPE, NYLON, TUNGSTEN, GLASS FIBER, SPANDEX.
COATING: NITRILE, SANDY FINISH. **REINFORCEMENT:** NITRILE

GAUGE:
18

SIZE RANGE:
HIGH CUT F GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

| SIZE | ARTICLE NUMBER | PACK QUANTITY | ARTICLE NUMBER | PACK QUANTITY |
|----------|----------------|---------------|----------------|---------------|
| 7 / S | 4932492040 | 1 | 4932492045 | 12 |
| 8 / M | 4932492041 | 1 | 4932492046 | 12 |
| 9 / L | 4932492042 | 1 | 4932492047 | 12 |
| 10 / XL | 4932492043 | 1 | 4932492048 | 12 |
| 11 / XXL | 4932492044 | 1 | 4932492049 | 12 |



**STAY SAFE.
STAY PRODUCTIVE.**


Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu




HIGH CUT F GLOVES

CARE INSTRUCTIONS

 WASHING, NORMAL PROCESS, MAXIMUM WASHING TEMPERATURE 40° CELSIUS

 NO CHEMICAL CLEANING

 DO NOT IRON

 DO NOT BLEACH

 NO TUMBLER

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.

 **STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu